



ISO 9001: 2000 - QUALITY ASSURANCE

Distributor & Fabricator of Engineered Plastic & Electrical Products

NEMA GPO-3 PULTRUDED ANGLES + CHANNELS

- NEMA GPO-3 Track Resistant, Flame Retardant
- UL Temperature 130C-degrees Class B rated
- UL 94V-0 Flammability Rated Self-Extinguishing
- Low Thermal Conductivity and Thermal Expansion values

Rectangular Tube

Part No.	Thickness	Leg	Width
F822024	1/8	1-1/2	1-1/2
F822432	1/4	2.00	2.00

Terminal Strips

Part No.	Thickness	Leg	Width
2700	1/8	1-1/4	3/8
2710	1/4	1-1/2	7/16
2720	1/2	2.00	-

Hat Shaped Channel

Part No.	Thickness	Leg	Width
1161	1/8	7/8	4-19/32
2091	1/8	1-3/8	5.00
1272	3/16	2-3/8	9-9/16

Equal Leg Angles

Part No.	Thickness	Leg	Width
2889	1/8	1-1/4	1-1/4
2879	3/16	1-1/4	1-1/4
2880	1/8	1-1/2	1-1/2
2881	3/16	1-1/2	1-1/2
2882	1/4	1-1/2	1-1/2
2883	3/16	2.00	2.00
2884	1/4	2.00	2.00
2885	1/4	3.00	3.00
2886	3/8	3.00	3.00
G3945	1/4	4.00	4.00

Channel

Part No.	Thickness	Leg	Width
2875	1/8	9/16	2.00
2617	1/8	13/16	2.00
1144	1/4	1.00	2.00
2261	1/16	3/4	2-3/16
2212	1/8	3/4	2-5/16
1177	1/8	1-7/32	2-9/16
1166	1/4	7/8	3.00
2888	1/4	1-1/2	3.00
1939	3/16	2-9/16	3-9/16
1791	1/8	1-1/8	3-19/32
1155	1/4	1-1/8	4.00
2242	3/16	1-3/8	4.00
2872	1/8	2-1/2	4-1/2
2874	1/4	2-1/2	4-1/2
1940	9/32	2-9/16	4-9/16
1788	3/16	1-5/8	4-3/4
2825	5/32	1-1/4	5-1/2
2288	9/32	2.00	6-3/8
1844	3/16	2-11/16	8-1/2
1936	1/8	1-5/8	9-21/32
2250	3/8	1-5/8	11-9/32
2120	5/32	1-7/16	11-1/2

Unequal Leg Angles

Part No.	Thickness	Leg	Width
1134 *	3/8	2.00	1-3/4
2891	1/2	3.00	2-1/4
2876	3/16	1-1/2	2-1/4
1133	3/16	1-1/4	2-1/4
2877	1/4	2.00	2-3/4
2890	1/2	3.00	6.00

* Also sold in 7' lengths